



Split and Brushed

# *Stormy Grey*

Quartz







1 Pool Surrounds

2 Outdoor Paving

3 Outdoor Paving

4 Outdoor Steps



Finish

Sawn	Honed	Flamed	Sandblasted	Natural Split and Brushed	Tumbled and Unfilled	Honed and Filled	Acid Wash & Tumbled
P5	P3	P5	P5	P5	P4	P2	P5
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

- ☒ Standard Stock
- ☒ Made to Order
- ☐ Not Available

Format

- ☒ Paving
- ☒ Coping
- ☐ Stepper
- ☐ Cobble
- ☐ Slab

Application

- ☒ Exterior Paving and Pathway
- ☒ Pool Surrounds
- ☒ Driveway
- ☒ Light Traffic
- ☒ Regular Traffic
- ☒ Commercial Area
- ☒ Interior Walling
- ☒ Exterior Walling
- ☒ Feature Walls

**Slip Rating**

P1 - Very low slip resistance

P2 - Low slip resistance

P3 - Moderate slip resistance

P4 - Good slip resistance

P5 - Very high slip resistance

**MTO - Made to Order**

Sealing Requirement

- ☐ Optional
- ☒ Recommended
- ☐ Required

Stone Properties

Slip Resistance	Salt Resistance	Abrasion	Strength	Water Absorption	Comprehensive Strength	Flexural Strength	Light Reflectance Value (LRV)
AS 4586	AS/NZS 4456.10						
P5	Exposure Grade						

Type and Size (mm)

Finish	Paver	Coping	Stepper	Cobbles	Walling	Slab
Split & Brushed	Crazy Pavingx20-30	MTO			MTO	



**Daily Maintenance**

- Sweep or use a leaf blower to remove dirt, leaves, and debris, especially in textured areas.
- Rinse with water to wash away dust and surface grime. Rain usually helps, but hosing occasionally maintains appearance.
- Avoid dragging heavy furniture or tools across the surface to prevent chipping on the split edges.
- Use rubber pads under pots, outdoor furniture, or metal items to avoid rust marks or scratches.

**Sealing**

- Quartzite is less porous than limestone or sandstone but still benefits from sealing—especially with a split and brushed finish, which has more surface area to trap dirt.
- Apply a high-quality penetrating (impregnating) sealer designed for natural stone.
- Seal upon installation and reapply every 1–2 years, depending on weather conditions and wear.
- A color-enhancing sealer may be used to deepen the tone and highlight the stone's texture (optional; test first).

**Cleaning**

- Clean with a pH-neutral stone cleaner or a mild soap diluted in water.
- Do not use acidic cleaners (vinegar, lemon, harsh grout cleaners), which will etch and damage the surface.
- Low to medium pressure washing is safe.
- For general cleaning, scrub gently with a soft bristle brush to reach into the brushed surface texture. Rinse thoroughly to avoid residue buildup.
- For stubborn stains, use a stone-safe poultice for oil, rust, or organic marks. Consider spot sealing after treating stains.

***SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!***

**Contact Us**

5 Hamilton Street  
VIC 3166  
Australia

1300 855 851  
[info@saistone.com.au](mailto:info@saistone.com.au)  
[saistone.com.au](http://saistone.com.au)

