



Sandblasted and Acid
Washed



Acid Washed

Santa Snow

Limestone



Finish

Sawn	Honed	Flamed	Sandblasted & Acid Washed	Rockface	Natrual Split & Tumbled	Honed and Tumbled	Acid Washed
P5	P3	P5	P5	P5	P5	P3	P5
☐	☐	☐	☒	☐	☐	☐	☒

- ☒ Standard Stock
- ☒ Made to Order
- ☐ Not Available

Format

- ☒ Paving
- ☒ Coping
- ☐ Stepper
- ☒ Cobble
- ☒ Slab

Slip Rating
P1 - Very low slip resistance
P2 - Low slip resistance
P3 - Moderate slip resistance
P4 - Good slip resistance
P5 - Very high slip resistance

Application

- ☒ Exterior Paving and Pathway
- ☒ Pool Surrounds
- ☒ Driveway
- ☒ Light Trafficce
- ☒ Regular Trafficce
- ☒ Commercial Area
- ☒ Interior Walling
- ☒ Exterior Walling
- ☒ Feature Walls

Sealing Requirement

- ☐ Optional
- ☐ Recommended
- ☒ Required

Stone Properties

Slip Resistance	Salt Resistance	Abrasion	Strength	Water Absorption	Comprehensive Strength	Flexural Strength	Light Reflectance Value (LRV)
-----------------	-----------------	----------	----------	------------------	------------------------	-------------------	-------------------------------

P4-P5

Exposure Grade

Type and Size (mm)

Finish	Paver	Coping	Stepper	Cobbles	Walling	Slab
All Finish	MTO	MTO		MTO	MTO	MTO



Daily Maintenance

- Sweep or blow off leaves, dust, and sand regularly to avoid surface abrasion.
- Rinse with a hose occasionally, especially in dusty or muddy areas.
- Avoid placing metal furniture directly on the surface to prevent rust stains.
- For outdoor kitchens or BBQ areas, wipe up oil and food spills promptly to avoid staining.

Sealing

- Limestone is highly porous, and the sandblasted finish increases absorption.
- Seal before or immediately after installation to prevent early staining.
- Reseal every 6–12 months, depending on exposure to sun, rain, foot traffic, and surrounding vegetation.
- Use a penetrating (impregnating) sealer that:
 - Is breathable (prevents moisture from being trapped),
 - Offers UV protection,
 - Is suitable for limestone and exterior use.
- Optionally, a color-enhancing sealer can bring out natural tones, but test first on a hidden section.

Cleaning

- Use a pH-neutral stone cleaner or mild detergent mixed with water.
- Do NOT use acidic cleaners like vinegar, lemon, or bleach – they will etch the stone.
- Soft scrubbing with a brush is fine for textured surfaces to remove dirt from grooves.
- Pressure wash only at low pressure, keeping the nozzle at a distance to avoid surface erosion.
- For stains:
 - Use a poultice for oil or rust stains (specific to limestone).
 - For algae, moss, or mildew, use a stone-safe outdoor biocide (avoid chlorine bleach).

SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!

Contact Us

5 Hamilton Street
VIC 3166
Australia

1300 855 851
info@saistone.com.au
saistone.com.au

