




Sawn



Honed



Sandblasted



Bush Hammered

Grace Black

Bluestone



Finish

Sawn	Honed	Flamed	Sandblasted	Rockface	Natural Split	Bush Hammered	Tumbled
P5	P3	P5	P5	P5	P5	P5	P5
☒	☒	☐	☒	☐	☐	☒	☒

- ☒ Standard Stock
- ☒ Made to Order
- ☐ Not Available

Format

- ☒ Paving
- ☒ Coping
- ☒ Stepper
- ☒ Cobble
- ☒ Slab

Application

- ☒ Exterior Paving and Pathway
- ☒ Pool Surrounds
- ☒ Driveway
- ☒ Light Traffic
- ☒ Regular Traffic
- ☒ Commercial Area
- ☒ Interior Walling
- ☒ Exterior Walling
- ☒ Feature Walls

Slip Rating

P1 - Very low slip resistance

P2 - Low slip resistance

P3 - Moderate slip resistance

P4 - Good slip resistance

P5 - Very high slip resistance

MTO - Made to Order

Sealing Requirement

- ☐ Optional
- ☒ Recommended
- ☐ Required

Stone Properties

Slip Resistance	Salt Resistance	Abrasion	Strength	Water Absorption	Comprehensive Strength	Flexural Strength	Light Reflectance Value (LRV)
-----------------	-----------------	----------	----------	------------------	------------------------	-------------------	-------------------------------

P2-P5

Exposure Grade

Type and Size (mm)

Finish	Paver	Coping	Stepper	Cobbles	Slab
--------	-------	--------	---------	---------	------

All Finish

MTO

MTO

MTO

MTO



Daily Maintenance

- Sweep or use a leaf blower to remove dirt, leaves, and debris, especially in textured areas.
- Rinse with water to wash away dust and surface grime. Rain usually helps, but hosing occasionally maintains appearance.
- Avoid dragging heavy furniture or tools across the surface to prevent chipping on the split edges.
- Use rubber pads under pots, outdoor furniture, or metal items to avoid rust marks or scratches.

Sealing

- Seal every 12–18 months with a penetrating sealer that is suitable for natural stone and exterior use.
- A color-enhancing sealer can enrich the natural dark tone and reduce patchiness (optional).

Cleaning

- Clean with a pH-neutral stone cleaner or a mild soap diluted in water.
- Do not use acidic cleaners (vinegar, lemon, harsh grout cleaners), which will etch and damage the surface.
- Low pressure washing is safe.
- For general cleaning, scrub gently with a soft bristle brush to reach into the brushed surface texture. Rinse thoroughly to avoid residue buildup.
- For stubborn stains, use a stone-safe poultice for oil, rust, or organic marks. Consider spot sealing after treating stains.

SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!

Contact Us

5 Hamilton Street
VIC 3166
Australia

1300 855 851
info@saistone.com.au
saistone.com.au

