



Flamed



Sandblasted



Honed



Bush Hammered

New Grey (New Quarry)

Granite



Finish

Honed	Flamed	Sandblasted	Rockface	Natural Split	Bush Hammered	Polished	Leathered
P3	P5	P5	P5	P5	P3	P5	P5
☒	☒	☐	☐	☐	☒	☒	☐

- ☒ Standard Stock
☒ Made to Order
☐ Not Available

Format

- ☒ Paving ☒ Coping ☒ Stepper ☒ Cobble ☒ Slab

Slip Rating

P1 - Very low slip resistance

P2 - Low slip resistance

P3 - Moderate slip resistance

P4 - Good slip resistance

P5 - Very high slip resistance

Application

- ☒ Exterior Paving and Pathway ☒ Pool Surrounds ☒ Driveway
☒ Light Traffic ☒ Regular Traffic ☒ Commercial Area
☒ Interior Walling ☒ Exterior Walling ☒ Feature Walls

Sealing Requirement

- ☐ Optional ☒ Recommended ☐ Required

Stone Properties

Slip Resistance	Salt Resistance	Abrasion	Strength	Water Absorption	Comprehensive Strength	Flexural Strength	Open Porosity
P2-P5	Exposure Grade						

Type and Size (mm)

Finish	Paver	Coping	Stepper	Cobbles	Slab
All Finish	MTO	MTO		MTO	MTO

Daily Maintenance

- Sweep or blow off leaves, dust, and sand regularly to avoid surface abrasion.
- Rinse with a hose occasionally, especially in dusty or muddy areas.
- Avoid placing metal furniture directly on the surface to prevent rust stains.
- For outdoor kitchens or BBQ areas, wipe up oil and food spills promptly to avoid staining.

Sealing

- Flamed granite is more porous than polished or honed granite due to its textured surface.
- Seal every 12 months or more frequently if the area is exposed to heavy traffic, grease, or constant moisture.
- Use a penetrating (impregnating) sealer made for textured, natural stone and outdoor use (UV- and weather-resistant).
- Optional: Use a color enhancer sealer if a darker or richer appearance is desired (test on a sample area first).

Cleaning

- Use a pH-neutral stone cleaner or diluted mild detergent (non-acidic, non-alkaline).
- Pressure washing is generally safe. Use low to medium pressure. Keep the nozzle at a reasonable distance to avoid surface damage.
- For stubborn stains, apply a poultice or stone-safe degreaser for oil-based stains. Use a specialized rust remover for iron stains—ensure it's safe for granite.
- Avoid:
 - Acidic cleaners (e.g., vinegar, lemon, acidic tile cleaners)
 - Harsh chemicals like bleach or ammonia
 - Abrasive brushes that may break down the stone surface over time

SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!

Contact Us

5 Hamilton Street
VIC 3166
Australia

1300 855 851
info@saistone.com.au
saistone.com.au

