



Sandblasted



Honed and Tumbled



Natural Split & Tumbled

Smooth Grey

Limestone



Finish

Sawn	Honed	Flamed	Sandblasted	Rockface	Natrual Split & Tumbled	Honed and Tumbled	Acid Washed
P5 ☐	P3 ☒	P5 ☐	P5 ☒	P5 ☐	P5 ☒	P5 ☒	P5 ☐

- ☒ Standard Stock
☒ Made to Order
☐ Not Available

Format

- ☒ Paving ☒ Coping ☐ Stepper ☒ Cobble ☒ Slab

Slip Rating

P1 - Very low slip resistance

P2 - Low slip resistance

P3 - Moderate slip resistance

P4 - Good slip resistance

P5 - Very high slip resistance

Application

- ☒ Exterior Paving and Pathway ☒ Pool Surrounds ☒ Driveway
☒ Light Trafficce ☒ Regular Trafficce ☒ Commercial Area
☒ Interior Walling ☒ Exterior Walling ☒ Feature Walls

Sealing Requirement

- ☐ Optional ☐ Recommended ☒ Required

Stone Properties

Slip Resistance	Salt Resistance	Abrasion	Strength	Water Absorption	Comprehensive Strength	Flexural Strength	Light Reflectance Value (LRV)
-----------------	-----------------	----------	----------	---------------------	---------------------------	-------------------	----------------------------------

P4-P5

Exposure Grade

Type and Size (mm)

Finish	Paver	Coping	Stepper	Cobbles	Walling	Slab
All Finish	MTO	MTO		MTO	MTO	MTO

Daily Maintenance

- Sweep or blow off leaves, dust, and sand regularly to avoid surface abrasion.
- Rinse with a hose occasionally, especially in dusty or muddy areas.
- Avoid placing metal furniture directly on the surface to prevent rust stains.
- For outdoor kitchens or BBQ areas, wipe up oil and food spills promptly to avoid staining.

Sealing

- Limestone is highly porous, and the sandblasted finish increases absorption.
- Seal before or immediately after installation to prevent early staining.
- Reseal every 6–12 months, depending on exposure to sun, rain, foot traffic, and surrounding vegetation.
- Use a penetrating (impregnating) sealer that:
 - Is breathable (prevents moisture from being trapped),
 - Offers UV protection,
 - Is suitable for limestone and exterior use.
- Optionally, a color-enhancing sealer can bring out natural tones, but test first on a hidden section.

Cleaning

- Use a pH-neutral stone cleaner or mild detergent mixed with water.
- Do NOT use acidic cleaners like vinegar, lemon, or bleach – they will etch the stone.
- Soft scrubbing with a brush is fine for textured surfaces to remove dirt from grooves.
- Pressure wash only at low pressure, keeping the nozzle at a distance to avoid surface erosion.
- For stains:
 - Use a poultice for oil or rust stains (specific to limestone).
 - For algae, moss, or mildew, use a stone-safe outdoor biocide (avoid chlorine bleach).

SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!

Contact Us

5 Hamilton Street
VIC 3166
Australia

1300 855 851
info@saistone.com.au
saistone.com.au

