



Coarse Honed

White Sand

Sandstone



Finish

Sawn	Coarse Honed	Flamed	Sandblasted	Rockface/ Natural Split	Tumbled and Unfilled	Honed and Filled	Acid Wash & Tumbled
P5 ☐	P3 ☒	P5 ☐	P5 ☐	P5 ☐	P4 ☐	P2 ☐	P5 ☐

- ☒ Standard Stock
☒ Made to Order
☐ Not Available

Format

- ☒ Paving ☒ Coping ☐ Stepper ☒ Cobble ☒ Slab

Slip Rating

P1 - Very low slip resistance

P2 - Low slip resistance

P3 - Moderate slip resistance

P4 - Good slip resistance

P5 - Very high slip resistance

Application

- ☒ Exterior Paving and Pathway ☒ Pool Surrounds ☒ Driveway
☒ Light Traffic ☒ Regular Traffic ☒ Commercial Area
☒ Interior Walling ☒ Exterior Walling ☒ Feature Walls

MTO - Made to Order

Sealing Requirement

- ☐ Optional ☐ Recommended ☒ Required

Stone Properties

Slip Resistance	Salt Resistance	Abrasion	Strength	Water Absorption	Comprehensive Strength	Flexural Strength	Light Reflectance Value (LRV)
-----------------	-----------------	----------	----------	------------------	------------------------	-------------------	-------------------------------

P3

Exposure Grade

Type and Size (mm)

Finish	Paver	Coping	Stepper	Cobbles	Walling	Slab
All Finish	MTO	MTO		MTO	MTO	MTO

Daily Maintenance

- Sweep or blow off leaves, dust, and grit regularly to avoid surface abrasion.
- Rinse with a hose occasionally to remove accumulated dirt, especially in outdoor or high-traffic areas.
- Use mats or pads under metal furniture and pots to prevent rust and scratches.
- Avoid dragging heavy objects directly on the surface to prevent chipping or flaking.
- Avoid dragging heavy objects across the surface to prevent edge chipping or cracking.

Sealing

- Sandstone is a highly porous stone that easily absorbs water, dirt, and stains if left unsealed
- Sealing is essential to protect against moisture, algae, and weathering.
- Apply a breathable penetrating/impregnating sealer suitable for porous natural stones.
- Perform initial sealing during or immediately after installation.
- Reapply sealer every 6–12 months, depending on weather exposure and usage.
- A color-enhancing sealer may be used to enrich the stone's natural tones—test in a small area first.

Cleaning

- Clean regularly with a pH-neutral stone cleaner or mild soap diluted in water.
- Do not use acidic or harsh chemical cleaners, which can erode or dull the surface.
- Low-pressure washing is suitable but avoid high-pressure jets, which can damage the stone's texture.
- For algae or moss, use a stone-safe biocide or outdoor mildew remover—avoid chlorine bleach
- For stubborn stains, use a suitable stone poultice and reseal the area afterward.

SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!

Contact Us

5 Hamilton Street
VIC 3166
Australia

1300 855 851
info@saistone.com.au
saistone.com.au

