




Sandblasted



Honed



Honed and Tumbled



Honed and Tumbled

# *Silver Grey*

Travertine



## Finish

| Bush-hammered                             | Honed                                     | Flamed                         | Sandblasted                               | Rockface/<br>Natural Split     | Tumbled and<br>Unfilled        | Honed and<br>Tumbled                     | Acid Wash &<br>Tumbled         |
|-------------------------------------------|-------------------------------------------|--------------------------------|-------------------------------------------|--------------------------------|--------------------------------|------------------------------------------|--------------------------------|
| P5<br><input checked="" type="checkbox"/> | P3<br><input checked="" type="checkbox"/> | P5<br><input type="checkbox"/> | P5<br><input checked="" type="checkbox"/> | P5<br><input type="checkbox"/> | P4<br><input type="checkbox"/> | P<br><input checked="" type="checkbox"/> | P5<br><input type="checkbox"/> |

- ☒ Standard Stock  
☒ Made to Order  
☐ Not Available

## Format

- ☒ Paving ☒ Coping ☒ Stepper ☒ Cobble ☒ Slab

## Slip Rating

P1 - Very low slip resistance

P2 - Low slip resistance

P3 - Moderate slip resistance

P4 - Good slip resistance

P5 - Very high slip resistance

## Application

- ☒ Exterior Paving and Pathway ☒ Pool Surrounds ☒ Driveway  
☒ Light Traffic ☒ Regular Traffic ☒ Commercial Area  
☒ Interior Walling ☒ Exterior Walling ☒ Feature Walls

**MTO - Made to Order**

## Sealing Requirement

- ☐ Optional ☐ Recommended ☒ Required

## Stone Properties

| Slip Resistance | Salt Resistance | Abrasion | Strength | Water<br>Absorption | Comprehensive<br>Strength | Flexural Strength | Light Reflectance<br>Value (LRV) |
|-----------------|-----------------|----------|----------|---------------------|---------------------------|-------------------|----------------------------------|
| P2 - P5         | A               |          |          |                     |                           |                   |                                  |

## Type and Size (mm)

| Finish     | Paver | Coping | Stepper | Cobbles | Walling | Slab |
|------------|-------|--------|---------|---------|---------|------|
| All Finish | MTO   | MTO    | MTO     | MTO     | MTO     | MTO  |



**Daily Maintenance**

- Sweep or blow off leaves, dust, and sand regularly to avoid surface abrasion.
- Rinse with a hose occasionally, especially in dusty or muddy areas.
- Use protective pads or mats under heavy or metal items to prevent rust and scratches.
- Avoid dragging furniture or pots directly across the surface to prevent chipping.

**Sealing**

- Travertine is very porous, and unfilled surfaces have open holes that easily trap dirt and absorb moisture.
- Sealing is essential to protect against stains, algae, and erosion.
- Apply a penetrating/impregnating sealer, specifically for exterior uses.
- Initial sealing should be done during or right after installation.
- Reseal every 6–12 months, depending on climate, use, and foot traffic.
- If you want a darker or “wet look,” use a color-enhancing sealer (always test first).

**Cleaning**

- Clean with a pH-neutral stone cleaner or a mild soap diluted in water.
- Do not use acidic cleaners (vinegar, lemon, harsh grout cleaners), which will etch and damage the surface.
- Low-pressure washing is safe.
- For algae, mold, or mildew, use a stone-safe outdoor biocide or mildew remover—avoid chlorine bleach.
- For stubborn stains, use a poultice specific to the stain type (oil, rust, etc.). Re-seal after treating stains.

***SAI Stone offers a wide range of cleaning and sealing products, as well as glue and grouting solutions. If you need more information or assistance, don't hesitate to reach out!***

**Contact Us**

5 Hamilton Street  
VIC 3166  
Australia

1300 855 851  
info@saistone.com.au  
saistone.com.au

